



Feigete Intelligent Technology Co., Limited

ADD: 2 Floor,Building No.51,Bantian No.3 Industrial Area,Longgang District,Shenzhen,China
 TEL:86-755-82338710 FAX:86-755-28751866

SFN100

10.1 Inch Android all in one desktop pos terminal



1. Parameters

Type	Project	Description
Configuration	CPU	Quad Core, 2.0GHz
	Memory	3GB+16GB internal memory (4+64GB as option)
	WiFi	2.4GHz/5GHz IEEE802.11 a/b/g/n/ac
	camera	5MP (13MP Optional), support for barcode/ qr code scanning
	3G	WCDMA B1/B2/B5/B8
	4G	FDD-LTE B1/B3/B5, TDD -LTE B38/B39/B40/B41
	2G	GSM B2/B3/B5/B8 CDMA 800
	OS	Android 11/12
Display	Screen	10.1 Inch, HD 800*1280 / FHD 1200*1920 (Optional)
	TP	Capacitive multipoint touch screen
	Language	English, French, German, Italian, Japanese, Korean, Russian, Spanish, Polish, Czech, Chinese ect.
Others	G-Sensor	support
	GPS	support GPS, GLONASS Galileo Beidou
	Printer	Paper width 58mm (80mm Optional) Max. Diameter of paper roll 60mm
	Chip card	Support ISO7816
	Contactless card	NFC 13.56MHz, ISO 14443 Type A & B, Mifare
	Magnetic card	Support ISO7811
	BT	support BT5.0
	Battery	5600mAh
	Facial	Optional
Fingerprint module	Optional	
Software Configuration	Audio format	MP3, MP2, AMR, AWB, APE, M4A, MIDI, OGG, WAV, FLAC, 3GP
	Video format	MPEG4-SP, H.264/AVC, H.263, 3GP, 3G2, MP4, MKV, AVI, WEBM
	Picture format	JPEG, BMP, PNG, GIF
	E-book format	TXT, PDF, FB2, EPUB
Device	Color	Black
	Physical button	x 1, power button
	Dimension and weight	Machine size: 262 x 263.5 x 91.5mm, 1.45kg/pc Package size: 35x15x39cm, 3.5kg/pc
	Temperature	Storage temperature: -10℃-60℃ Working Temperature: 0℃-40℃
Power adapter	Input: 110V to 240V AC Output: 12V DC / 3A	
Interface	SIM	X 2
	PSAM	X 2
	Micro SD	Support SD3.0, up to 128GB
	USB 2.0	USB Type A x 4; USB Type C x 1
	DC Port	12V 3A
	RJ12	X 1
	RJ11	X 1
	RJ45	X 1
	Mini USB	X 1
	DC Port	12V 3A
Package	1 x Terminal	
	1 x adapter	
	1 x User's Manual	
	1 x Paper roll	